

BO2015NBH2B $\varnothing 20\text{mm} \times 15.1\text{mm}$, 外转子带传感器 Outer Rotor, Sensored

应用领域：无人机云台、激光雷达、激光扫描、手持云台。

Applications: UAV gimbals, LiDAR, laser scanner, handheld gimbals.

				22-113-6.0	03-113-12.0	19-113-24.0
电机参数 / Motor Data						
1	电压	Voltage	V	6.0	12.0	24.0
2	端电阻	Terminal resistance	Ω	0.98	3.8	17.1
3	空载转速	No-load speed	rpm	11300	11300	11300
4	空载电流	No-load current	A	0.16	0.08	0.04
5	堵转转矩	Stall torque	mNm	29.2	30.4	26.8
6	堵转电流	Stall current	A	6	3.2	1.4
7	额定转矩	Nominal torque	mNm	9.1	9.1	9.1
8	额定转速	Nominal speed	rpm	7790	6440	7450
9	额定电流	Nominal current	A	2	1	0.5
10	最大输出功率	Max. output power	W	8.7	9	7.9
11	最大效率	Max. efficiency	%	70	71	69
12	反电势常数	Back-EMF constant	mV/rpm	0.5	1	2
13	转矩常数	Torque constant	mNm/A	4.9	9.9	17.7
14	电感	Terminal inductance	mH	0.15	0.63	2.52
15	转速 / 转矩斜率	Speed/torque gradient	rpm/mNm	385	370	420
16	转子惯量	Rotor inertia	gcm^2	6.7	6.7	6.7
17	重量	Weight	g	21	21	21

热参数 / Thermal Data				特性曲线 / Characteristics Curve
18	热阻 (机壳 - 环境)	Thermal resistance housing-ambient	K/W	9.5
19	热阻 (线圈 - 机壳)	Thermal resistance winding-housing	K/W	8
20	热时间常数 (电机)	Thermal time constant motor	s	354
21	热时间常数 (线圈)	Thermal time constant winding	s	23
22	工作温度范围	Operating temperature range	$^{\circ}\text{C}$	$-40 \sim +120$
23	绕组耐温等级	Thermal class of winding	$^{\circ}\text{C}$	155

机械参数 / Mechanical Data			
24	轴向间隙	Axial play	mm
25	径向间隙	Radial play	mm
26	动态轴向载荷	Axial load dynamic	N
27	静态轴向载荷	Axial load static	N
28	径向载荷 (距安装面 3mm)	Radial load at 3 mm from mounting face	N

其它参数 / Other Specifications			
29	极对数	No. of pole pairs	4
30	滚珠轴承	Ball bearings	2
31	换向结构	Commutation structure	hall sensor
32	防护等级	Protection class	IP20

可选配置 / Options

齿轮箱：行星齿轮 齿轮组主要技术指标详见第 156 页
 Gearbox: planetary gearbox the main technical parameters are detailed on page 156

性能 Special coils: 连续运行范围内可定制 customizable in continuous operation range

编码器 Encoder/ 驱动器 Driver: 可定制 customizable upon request

法兰 Flange: 标准前后法兰 standard front and rear flanges / 定制法兰 custom flanges



轴 Shaft: 长度 length / 异形 shape

轴承类型 Bearing type: 含油轴承 sleeve bearings / 滚珠轴承 ball bearings

电气连接 Electrical connection: 端子或导线 connector or wire / 导线长度 lead wires length

端子定义 / Connection			
A 霍尔传感器 / hall sensor		B 无传感器 / sensorless	
FPC		FPC	
Pin1	H+	Pin1	U
Pin2	Hw	Pin2	V
Pin3	Hu	Pin3	W
Pin4	Hv		
Pin5	H-		
Pin6	W		
Pin7	V		
Pin8	U		

外观图 / Outline Drawing



规格如有变更，恕不另行通知。Specification subject to change without notice.

www.constarmotor.com

精密直流空心杯电机
PRECISION DC CORELESS MOTOR

无刷电机
BRUSHLESS DC MOTOR

驱动器
CONTROLLER

精密齿轮减速电机
PRECISION GEAR MOTOR

精密伺服电机
PRECISION SERVO MOTOR

直流空心杯电机
DC CORELESS MOTOR

直流铁芯电机
DC CORE MOTOR

声波振动电机
SONIC MOTOR

全球营销网络
GLOBAL MARKETING NETWORK