

L0616...06PP... | L0616...06PF... | L0616...06PR...

∅6mm, 行星齿轮系列 Planetary Gearbox Series


应用领域：医疗器械、安防设备、视像产品、高端智能电玩、个人保健产品等领域。

Applications: medical equipment, security systems and locks, audio and visual products, personal healthcare products, and high-end hobby products.

				L0616-1300-3.0 -06PP25-0001	L0615-1300-3.0 -06PF25-0025	L0615-1800-3.0 -06PR25-0035
电机参数 / Motor Data						
1	电压	Voltage	V	3.0	3.0	3.0
2	端电阻	Terminal resistance	Ω	13.7	13.7	7.8
3	空载转速	No-load speed	rpm	1300	1300	1750
4	空载电流	No-load current	mA	50	50	55
5	最大转矩	Max torque	mNm	2.94	2.94	3.4
6	负载转矩	Load torque	mNm	0.2	0.2	0.2
7	负载转速	Load speed	rpm	1210	1200	1680
8	负载电流	Load current	mA	60	60	65
9	减速比	Reduction ratio		1/25	1/25	1/25
10	重量	Weight	g	1.2	1.2	1.2
11	工作温度范围	Operating temperature range	°C	-10~+70	-10~+70	-10~+70

特性曲线 / Characteristics Curve

L0616-1300-3.0-06PP25-0001



— 转速 (N) — 电流 (I)

仅供参考，详细了解请以产品规格书为准。
For reference only, please refer to the product specification.

可选配置 / Options

性能 Special coils: 连续运行范围内可定制 customizable in continuous operation rang

法兰 Flange: 标准前后法兰 standard front and rear flanges / 定制法兰 custom flanges

电气连接 Electrical connection: 端子或导线 connector or wire / 导线长度 lead wires length

外观图 / Outline Drawing

